

Three Pole Definite Purpose Contactors with AC Coil (Open Type only)

Full Load Amps	Locked Rotor Amps			Resistive Amps ②	Maximum Horsepower ②						Catalog Number	Price Each	Std. Pkg.	
					1Ø			3Ø						
	240V ②	480V	600V		120V	200	240V	200V	240V	480V				600V
30 ①	180	150	120	40	2	~	5	10	10	15	20	CDP2-B3P30A-* ④	111.00	25
40	240	200	160	50	3	~	7-1/2	10	10	20	25	CDP2-B3P40A-* ⑤	134.96	25
50	300	250	200	65	3	7-1/2	10	15	15	25	25	CDP2-C3P50A-*	259.03	15
60	360	300	240	75	5	7-1/2	10	25	25	30	30	CDP2-C3P60A-*	300.38	15
75	450	375	300	93	5	10	15	20	25	40	40	CDP2-D3P75A-*	391.81	1
90	540	450	360	120	7-1/2	15	20	25	30	50	50	CDP2-D3P90A-*	542.00	1



Series CDP2 3-pole contactor

Auxiliary Contacts for 3 Pole Contactors ⑦

Auxiliary	Description	Circuit Diagram	Catalog Number	Price
	Two pole Auxiliary Contact Block (1-NO / 1-NC) - Side mount with quick connect stabs for 25...40A, 3 pole contactors for 50...90A, 3 pole contactors		CDP2-BE-11 ⑥	42.44
			CDP2-CD-11 ⑥	43.87
	One pole Auxiliary Contact Block (SPDT) - Side mount with quick connect stabs for 25...40A, 3 or 4 pole contactors		CDP2-BE-1SPDT ⑥	37.45

AC Coil Codes

AC Coil Code	Voltage Range
	60 Hz
24	24V
120	120V
220W	208-240V
277	277V
480	480V

Ordering Instructions

Specify Catalog Number	
Replace (*) with Coil Code	See Coil Codes on this page

- ① 25A contactors available by special order. Contact your Sprecher + Schuh representative.
- ② 240V rating also applies to 277V applications.
- ③ Box lugs are supplied as standard. Screw terminals are available on the power connections by special order only in quantity.
- ④ Screw power terminals are supplied standard on 25 and 30A contactors. Box Lugs available by special order only in quantity.
- ⑤ Meets NEMA Standard B600. See page A7 for technical details.
- ⑥ Meets NEMA Standard B600 EXCEPT has 10 A continuous current rating.
- ⑦ A maximum of two auxiliary contacts can be installed on the contactor, one contact block on each side.





Four Pole Definite Purpose Contactors With AC Coil (Open Type only)

Full Load Amps	Locked Rotor Amps			Resistive Amps ②	Maximum Horsepower ③					Catalog Number	Price Each	Std. Pkg.
	240V ④	480V	600V		1Ø		3Ø					
					120V	240V	200V	240V	480V			
30 ①	180	150	120	40	2	5	10	10	15	CDP2-E4P30A-Q ⑤	128.43	20
40	240	200	160	50	3	7-1/2	10	10	20	CDP2-E4P40A-Q ⑤	149.10	20



Series CDP2 4-pole contactor

Auxiliary Contacts for 4 Pole Contactors ⑥

Auxiliary	Description	Circuit Diagram	Catalog Number	Price
	Two pole Auxiliary Contact Block (1-NO / 1-NC) - Side mount with quick connect stabs for all 4 pole contactors		CDP2-BE-11	42.44
	One pole Auxiliary Contact Block (SPDT) - Side mount with quick connect stabs for all 4 pole contactors		CDP2-BE-1SPDT	37.45

A.C. Coil Codes

AC Coil Code	Voltage Range
	60 Hz
24	24V
120	120V
220W	208-240V
277	277V
480	480V

Ordering Instructions

Specify Catalog Number	
Replace (*) with Coil Code	See Coil Codes on this page

- ① 25A contactors available by special order. Contact your Sprecher + Schuh representative.
- ② 240V rating also applies to 277V applications.
- ③ Box Power Lugs are supplied as standard. Screw terminals are available on the power connections by special order only in quantity.
- ④ Screw per terminals are supplied standard on 25 and 30A contactors. Box Lugs available by special order only in quantity.
- ⑥ A maximum of two auxiliary contacts can be installed on the contactor, one contact block on each side.