


### Three Phase, Reversing CAU7 & CAU9

Continuous Amp Rating - UL/CSA - Enclosed	Maximum Horsepower Three Phase				Auxiliary Contacts per Contactor ⑤		Type 1 General Purpose Catalog Number	Price	DIM	Type 12 [Type 3R ⑥] Industrial Dusttight Catalog Number	Price	DIM
	200V	230V	460V	575V	NO	NC ⑦						
25	2	2	5	7.5	1	1	CAU7-9-*G0 ⑧	574.36	A	CAU7-9-*D0 ⑧	632.62	M
25	3	3	7.5	10	1	1	CAU7-12-*G0 ⑧	646.93	A	CAU7-12-*D0 ⑧	697.00	M
30	5	5	10	15	1	1	CAU7-16-*G0 ⑧	688.83	A	CAU7-16-*D0 ⑧	737.88	M
30	5	7.5	15	15	1	1	CAU7-23-*G0 ⑧	707.22	A	CAU7-23-*D0 ⑧	782.85	M
55	7.5	10	20	25	1	1	CAU7-30-*G0 ⑧	824.75	A	CAU7-30-*D0 ⑧	873.81	M
60	10	10	25	30	1	1	CAU7-37-*G0 ⑧	907.54	A	CAU7-37-*D0 ⑧	1,032.22	M
75	10	15	30	30	1	1	CAU7-43-*G0 ⑧	973.97	B	CAU7-43-*D0 ⑧	1,099.67	M
75	15	20	40	40	1	1	CAU7-55-*G0 ⑧	1,046.53	B	CAU7-55-*D0 ⑧	1,172.23	M
90	15	20	40	50	1	1	CAU7-60-*G0 ⑧	1,298.96	C	CAU7-60-*D0 ⑧	1,324.51	O
90	20	25	50	60	1	1	CAU7-72-*G0 ⑧	1,415.47	C	CAU7-72-*D0 ⑧	1,441.02	O
100	25	30	60	60	1	1	CAU7-85-*G0 ⑧	1,523.80	C	CAU7-85-*D0 ⑧	1,548.33	O
120	30	30	75	75	1	1	CAU7-97-*G0 ⑧	1,760.91	C	CAU7-97-*D0 ⑧	1,786.46	O
116	30	40	75	100	1	1	CAU9-116-*G0 ⑨	2,739.98	E	CAU9-116-*D0 ⑨	2,910.66	Q
146	40	50	100	125	1	1	CAU9-146-*G0 ⑨	3,178.42	E	CAU9-146-*D0 ⑨	3,376.69	Q
190	50	60	125	150	1	1	CAU9-190-*G0 ⑨	3,962.29	E	CAU9-190-*D0 ⑨	4,266.85	R
205	60	75	150	200	1	1	CAU9-205-*G0 ⑨	5,479.96	F	CAU9-205-*D0 ⑨	5,978.70	T
265	75	100	200	250	1	1	CAU9-265-*G0 ⑨	5,827.44	F	CAU9-265-*D0 ⑨	6,300.63	T
305	100	125	250	300	1	1	CAU9-305-*G0 ⑨	6,527.51	H	CAU9-305-*D0 ⑨	7,005.81	H
370	125	150	300	350	1	1	CAU9-370-*G0 ⑨	7,506.59	H	CAU9-370-*D0 ⑨	8,056.43	H
400	125	150	350	400	1	1	CAU9-400-EI-*G0	10,538.86	R/F	CAU9-400-EI-*D0	10,954.82	R/F
460	150	200	400	500	1	1	CAU9-460-EI-*G0	12,752.52	R/F	CAU9-460-EI-*D0	13,255.34	R/F
480	200	250	500	600	1	1	CAU9-580-EI-*G0	16,577.86	R/F	CAU9-580-EI-*D0	17,231.94	R/F
750	250	300	600	700	1	1	CAU9-750-EI-*G0	21,716.48	R/F	CAU9-750-EI-*D0	22,572.91	R/F
860	~	400	800	1000	1	1	CAU9-860-EI-*G0	29,716.48	R/F	CAU9-860-EI-*D0	30,474.00	R/F
1060	~	450	900	1150	1	1	CAU9-1060-EI-*G0	32,835.84	R/F	CAU9-1060-EI-*D0	34,130.71	R/F

**NOTE:** Catalog numbers and enclosure dimensions reflect contactors with AC coils. For DC coils, select Coil Code from the DC Coil Code table on page C104 and follow the instructions for modifying catalog numbers.



### Ordering Instructions

Specify Catalog Number	
Replace (*) with Coil Code Factory Modifications available	Refer to page C104 Refer to pages C107-C111

- ① Dimensional information starts on page C122.
- ② For Type 3R outdoor applications, replace "D" in catalog number with an "R". Dimensions may change. For example catalog number CAU7-23-\*D0 becomes CAU7-23-\*R0. Price remains the same.
- ③ Contactors are equipped with number and type of auxiliaries indicated. See page C108 to order additional or different auxiliary contacts.
- ④ One N.C. auxiliary contact is used for electrical interlocking. On CAU7 reversing contactors, the N.C. contact comes from the Mechanical/Electrical Interlock unit (Cat # CM7-02).
- ⑤ CAU9-116...CAU9-370 contactors are available with "EI" option for PLC interface. Change catalog number to include "-EI". Example: CAU9-116-\*G0 becomes CAU9-116-EI-\*G0. See page C104 for price adder.

Enclosed Contactors