


### Series CATN7 575V AC with Thermal-Magnetic Circuit Breaker

NEMA Size	Max HP 3-Phase ①	Auxiliary Contacts per Contactor ②		MCCB Amps	Type 1 Metallic General Purpose Ⓞ (except TBH) Catalog No.	Price ③	DIM	Type 3R Metallic Outdoor Raintight Catalog No.	Price ③	DIM
		NO	NC							
00	0.25	2	1	15	CATN7-12-XD-D1BB-TBH15G17-L11	1925	C2	CATN7-12-XD-D1BB-TBH15R17-L11	2274	0
	0.5	2	1	15	CATN7-12-XD-D1CB-TBH15G17-L11	1925	C2	CATN7-12-XD-D1CB-TBH15R17-L11	2274	0
	0.75	2	1	15	CATN7-12-XD-D1CB-TBH15G17-L11	1925	C2	CATN7-12-XD-D1CB-TBH15R17-L11	2274	0
	1	2	1	15	CATN7-12-XD-D1CB-TBH15G17-L11	1925	C2	CATN7-12-XD-D1CB-TBH15R17-L11	2274	0
	2	2	1	15	CATN7-12-XD-D1CB-TBH15G17-L11	1925	C2	CATN7-12-XD-D1CB-TBH15R17-L11	2274	0
0	3	2	1	15	CATN7-16-XD-D1DB-TBH15G17-L11	1967	C2	CATN7-16-XD-D1DB-TBH15R17-L11	2316	0
	5	2	1	15	CATN7-16-XD-D1DB-TBH15G17-L11	1967	C2	CATN7-16-XD-D1DB-TBH15R17-L11	2316	0
1	7.5 ④	2	1	20	CATN7-37-XD-D1ED-TB20G17-L11	2180	C2	CATN7-37-XD-D1ED-TB20R17-L11	2572	0
	10 ④	2	1	20	CATN7-37-XD-D1FD-TB20G17-L11	2180	C2	CATN7-37-XD-D1FD-TB20R17-L11	2572	0
	7.5	2	1	20	CATN7-37-XD-D1ED-TBH20G17-L11	2332	C2	CATN7-37-XD-D1ED-TBH20R17-L11	2724	0
	10	2	1	20	CATN7-37-XD-D1FD-TBH20G17-L11	2332	C2	CATN7-37-XD-D1FD-TBH20R17-L11	2724	0
2	15 ④	2	1	35	CATN7-43-XD-D1FD-TB35G17-L11	2222	C2	CATN7-43-XD-D1FD-TB35R17-L11	2785	0
	20 ④	2	1	40	CATN7-43-XD-D1FD-TB40G17-L11	2222	C2	CATN7-43-XD-D1FD-TB40R17-L11	2785	0
	25 ④	2	1	50	CATN7-43-XD-D1FD-TB50G17-L11	2222	C2	CATN7-43-XD-D1FD-TB50R17-L11	2785	0
	15	2	1	35	CATN7-43-XD-D1FD-TBH35G17-L11	2375	C2	CATN7-43-XD-D1FD-TBH35R17-L11	2937	0
	20	2	1	40	CATN7-43-XD-D1FD-TBH40G17-L11	2375	C2	CATN7-43-XD-D1FD-TBH40R17-L11	2937	0
	25	2	1	50	CATN7-43-XD-D1FD-TBH50G17-L11	2375	C2	CATN7-43-XD-D1FD-TBH50R17-L11	2937	0
3	30 ④	2	1	60	CATN7-85-XD-EGE-TB60G17-L11	2538	D3	CATN7-85-XD-EGE-TB60R17-L11	4086	0
	40 ④	2	1	80	CATN7-85-XD-EGE-TB80G17-L11	2538	D3	CATN7-85-XD-EGE-TB80R17-L11	4086	0
	50 ④	2	1	100	CATN7-85-XD-EGE-TB100G17-L11	2690	D3	CATN7-85-XD-EGE-TB100R17-L11	4238	0
	30	2	1	60	CATN7-85-XD-EGE-TBH60G17-L11	2690	D3	CATN7-85-XD-EGE-TBH60R17-L11	4238	0
	40	2	1	80	CATN7-85-XD-EGE-TBH80G17-L11	2690	D3	CATN7-85-XD-EGE-TBH80R17-L11	4238	0
	50	2	1	100	CATN7-85-XD-EGE-TBH100G17-L11	2690	D3	CATN7-85-XD-EGE-TBH100R17-L11	4238	0

- Full Voltage Non-Reversing (FVNR) Features include:**
- NEMA-sized CAN7 contactor
  - Three-Phase CEP7 Electronic Overload Relay
  - Control Circuit Transformer
  - Hand-Off-Auto (H-O-A) selector switch
  - Red Run pilot light
  - 2-NO and 1-NC auxiliaries for customer use
  - Class CC Fuse holder as fused primary of CCT
  - Reset pushbutton
  - UL489 600V class thermal-magnetic molded case circuit breaker

**NEMA Combination Starters**



① HP and NEMA size selection shown for 575V ratings only. Contact your Sprecher + Schuh representative for other voltage applications.

② Contactors are equipped with number and type of auxiliaries indicated. See page C108 to order additional or different auxiliary contacts.  
 ③ Dimensional information starts on page C122.  
 ④ Applicable to 600Y/347V only.