










Control Modules

Module	Description	For use with...	Connection Diagrams	Function	Catalog Number
	Pneumatic Timing Module – The contacts in the Pneumatic Timing Element switch after the delay time. The contacts on the relay continue to operate without delay. <ul style="list-style-type: none"> • Continuous adjustment range 	CS7 all ①		ON-Delay .3...30s 1.8...180s	CZE7-30 CZE7-180
				OFF-Delay 0.3...30s 1.8...180s	CZA7-30 CZA7-180
	Electronic Timing Module – ① ON-Delay The relay is energized at the end of the delay time.	CS7 with 110...240V, 50/60Hz or 110...250V DC		110...240V 50/60Hz 110...250V DC 0.1...3s 1...30s 10...180s	CRZE7-3-110/240 CRZE7-30-110/240 CRZE7-180-110/240
		CS7 with 24...48V DC		24...48V DC 0.1...3s 1...30s 10...180s	CRZE7-3-24/48VDC CRZE7-30-24/48VDC CRZE7-180-24/48VDC
	Electronic Timing Module – ① OFF-Delay After interruption of the control signal, the relay is de-energized at the end of the delay time.	CS7 with 24V, 50/60Hz		110...240V 50/60Hz 0.3...3s 1...30s 10...180s	CRZA7-3-110/240 CRZA7-30-110/240 CRZA7-180-110/240
		CS7 with 110...240V, 50/60Hz		24V AC 50/60Hz 0.3...3s 1...30s 10...180s	CRZA7-3-24VAC CRZA7-30-24VAC CRZA7-180-24VAC

① Cannot be used with side-mounted auxiliary contacts on CS7 relays with DC coils.