







Beacons G 120 mm ø CE

Type	Description	Specifications	Catalog Number ①		Price
			Grey Housing	Black Housing	
	WLG Steady Beacon (no bulb) ②	up to 250 V AC/DC	822 100 900	822 500 900	66.39
	FLG Strobe Beacon (Xenon tube included)	24 V AC/DC, ~5 J 110/120 V AC, ~5 J 230/240 V AC, ~5 J	842 140 405 842 130 310 842 130 313	842 540 405 842 530 310 842 530 313	190.31
	DLG LED-Steady Beacon <i>amber, red or yellow only</i>	24 V AC/DC 48 V AC/DC 110/120 V AC 230/240 V AC	827 100 405 827 100 408 827 100 310 827 100 313	827 500 405 827 500 408 827 500 310 827 500 313	292.10
	BLG LED-Flashing Beacon <i>amber, red or yellow only</i>	24 V AC/DC 48 V AC/DC 110/120 V AC 230/240 V AC	807 100 405 807 100 408 807 100 310 807 100 313	807 500 405 807 500 408 807 500 310 807 500 313	331.93
	Bracket for all "G" models		822 200 900	822 200 900	30.98

Strobe Beacons Z CE


Type	Description	Specifications		Catalog Number		Price
		Voltage/Strobe	Lens Color	Dark Grey Housing		
	BZG Strobe Beacon Xenon tube included	24 V DC, 15 J	Amber	741 041 005	600.14	
			Red	741 042 005		
Yellow	741 047 005					
		230/240 V AC, 15 J	Amber	741 031 313	600.14	
			Red	741 032 313		
			Yellow	741 037 313		

① To complete the catalog no., replace the ① with one of the following numbers for desired lens color:
 1 = Amber, 2 = Red, 4 = Clear, 5 = Blue, 6 = Green, 7 = Yellow.


② Bulb not included. Order separately on page J39.




LED Flashing Beacon BC €€

Type	Description	Specifications		Catalog Number		Price
		Voltage	Lens Color	Red Housing	White Housing	
	BC1 Integrated LED Flashing Beacon Available in amber or red lens only	24 V DC	Red	C112 622 005	C112 222 005	77.01
		24 V DC	Amber	C112 621 005	C112 221 005	


Strobe Beacon XB2 €€

Type	Description	Specifications	Catalog Number	Price
	XB2 Strobe Beacon Xenon tube included Amber, Red and Blue Only	Replace with lens color	Black Housing ①	43.37
		12 V DC, 2 J	D118 52③ 004 ②	
		24 V DC, 2 J	D118 52③ 005	
		24 V AC, 2 J	D118 52③ 305	
		230 V AC, 2 J	D118 52③ 313	

Strobe Beacon Signalling Sounder €€

Type	Description	Specifications	Catalog Number	Price
	VS4 Strobe Beacon Signalling Sounder Not available in yellow 230/240 V AC		Black Housing	R/F
		Amber	410 401 005	
		Red	410 402 005	
		Clear	410 404 005	
		Blue	410 405 005	
		Green	410 406 005	

LED Flashing Multi-tone Siren €€



Type	Description	Specifications	Catalog Number		Price
			Red Housing	White Housing	
	CS1 LED Flashing Multi-tone Siren Not available in green or yellow 24 V DC	Amber	C111 621 005	C111 221 005	262.11
		Red	C111 622 005	C111 222 005	

- ① To complete the catalog no., replace the ③ with one of the following numbers for desired lens color:
1 = Amber, 2 = Red, 4 = Clear, 5 = Blue, 6 = Green, 7 = Yellow.
- ② Special order only. Minimum quantities apply. Contact Sprecher + Schuh for more information.





Mini Horn-Signal Beacons

CE

Type	Description	Specifications	Catalog Number	Price
	Replace ☼ with lens color		Grey Housing ①	
	KLL Mini Horn Signal Beacon with cone Steady of Flashing (no bulb) ② ③ 92 dB @ VDC 88 dB @ VAC, 50 Hz	24 V DC 24 V AC, 50 Hz 48 V AC, 50 Hz 120 V AC, 60 Hz 230 V AC, 50 Hz	710 11☼ 005 710 11☼ 105 710 11☼ 108 710 11☼ 210 710 11☼ 113	150.39
	KLF Mini Horn Strobe Beacon with cone Xenon tube included ③ 92 dB @ VDC 88 dB @ VAC, 50 Hz	24 V DC 110/120 V AC, 60 Hz 230/240 V AC, 50 Hz	710 12☼ 005 710 12☼ 210 710 12☼ 113	227.73
	KDL Mini Horn Signal Beacon without cone Steady of Flashing (no bulb) ② ③ 92 dB @ VDC 88 dB @ VAC, 50 Hz	24 V DC 24 V AC, 50 Hz 48 V AC, 50 Hz 120 V AC, 60 Hz 230 V AC, 50 Hz	710 01☼ 005 710 01☼ 105 710 01☼ 108 710 01☼ 210 710 01☼ 113	154.90
	KDF Mini Horn Strobe Beacon without cone Xenon tube included ③ 92 dB @ VDC 88 dB @ VAC, 50 Hz	24 V DC 110/120 V AC, 60 Hz 230/240 V AC, 50 Hz	710 02☼ 005 710 02☼ 210 710 02☼ 113	230.14

Mini Horns

CE

Type	Description	Specifications	Catalog Number	Price
			Grey Housing	
	KLH Mini Horn with cone continuous tone 92 dB @ VDC 88 dB @ VAC, 50 Hz	12 V DC	710 100 004	79.66
		24 V DC	710 100 005	
		110 V DC	710 100 010	
		220 V DC	710 100 013	
		24 V AC, 50 Hz	710 100 105	
		48 V AC, 50 Hz	710 100 108	
		110 V AC, 50 Hz	710 100 110	
230 V AC, 50 Hz	710 100 113			
	KDH Mini Horn without cone continuous tone 92 dB @ VDC 88 dB @ VAC, 50 Hz	12 V DC	710 000 004	72.58
		24 V DC	710 000 005	
		110 V DC	710 000 010	
		220 V DC	710 000 013	
		24 V AC, 50 Hz	710 000 105	
		48 V AC, 50 Hz	710 000 108	
		110 V AC, 50 Hz	710 000 110	
230 V AC, 50 Hz	710 000 113			

① To complete the catalog no., replace the ☼ with one of the following numbers for desired lens color:

1 = Amber, 2 = Red, 7 = Yellow.



② Bulb not included. Order separately on page J39.

③ Other voltages and colors available by special order only. Contact factor for more information.




Non-UL Signaling



Signal Horns **CE**

Type	Description	Specifications	Catalog Number	Price
		1	Grey Housing	
	HPT Signal Horn Impact resistant synthetic housing continuous tone (108 dB)	24 V DC 110 V DC 220 V DC 24 V AC, 50 Hz 48 V AC, 50 Hz 110 V AC, 50 Hz 230 V AC, 50 Hz 120 V AC, 60 Hz 240 V AC, 60 Hz	712 100 005 712 100 010 712 100 013 712 100 105 712 100 108 712 100 110 712 100 113 712 100 211 712 100 213	287.68
	HTG Signal Horn Die-cast aluminum housing continuous tone (108 dB)	24 V DC 110 V DC 220 V DC 24 V AC, 50 Hz 48 V AC, 50 Hz 110 V AC, 50 Hz 230 V AC, 50 Hz 120 V AC, 60 Hz 240 V AC, 60 Hz	713 100 005 713 100 010 713 100 013 713 100 105 713 100 108 713 100 110 713 100 113 713 100 211 713 100 214	531.09


Motor Sirens **CE**

Type	Description	Specifications	Catalog Number	Price
			Dark Grey Housing	
	SE1 Motor Siren 112 dBA max.	12 V AC/DC 230 V AC/DC	593 003 404 593 004 413	1150.70
	SE2 Motor Siren 110 dBA max.	12 V AC/DC 24 V AC/DC	593 005 404 593 005 405	3456.54
	Protection Hood for SE2		594 001 000	258.47
	SE3 Motor Siren 110 dBA max.	230 V AC/DC	593 009 413	4425.78
	Protection Hood, SE3		594 003 000	730.25


1 Other voltages available by special order only. Contact factory for more information.





Signal Bells CE

Type	Description	Specifications	Catalog Number		Price
			Grey Housing	Red Housing	
 <p>Signal Bells BEL Bell tone or quick beat (106 dB)</p>		24 V AC 115 V AC 230 V AC	720 300 105 720 300 110 720 300 313		R/F
		12 V DC 24 V DC	720 300 004 720 300 005	720 400 005	R/F

Electronic Multi-tone Sirens CE

Type	Description	Specifications	Catalog Number		Price
			Red Housing	White Housing	
	ES1	24 V DC, 32 tones (106 dB)	C110 620 005	C110 220 005	99.14
	ES2	110 - 230 V AC, 32 tones (106 dB)	C115 600 113	C115 200 113	243.42

Electronic Sounders CE





Type	Description	Specifications	Catalog Number		Price
			Type D (DIP Switch)	Type K (Terminals)	
 <p>EHS-D EHS-K Electronic Sounder swiveling speaker (118 dB)</p>		12-24 V AC/DC 110/120 V AC, 40-60 Hz 230/240 V AC, 40-60 Hz	731 010 405 731 010 310 731 010 313	731 020 405 731 020 310 731 020 313	1040.06
	 <p>EHL-D EHL-K Electronic Sounder short fixed speaker (110 dB)</p>		12-24 V AC/DC 110/120 V AC, 40-60 Hz 230/240 V AC, 40-60 Hz	730 010 405 730 010 310 730 010 313	730 020 405 730 020 310 730 020 313

Non-UL Signaling J




M28 Panel Mount Alarms



Type	Description	Specifications	Catalog Number		Price
			Grey Housing	Black Housing	
	ESD Panel Mount Alarm continuous tone (90 dB)	24 V AC/DC 48 V AC/DC 230/240 V AC	810 000 405 810 000 408 810 000 313	810 100 405 810 100 408 810 100 313	67.68
	ESP Panel Mount Alarm pulsing tone (90 dB)	24 V AC/DC 48 V AC/DC 230/240 V AC	811 000 405 811 000 408 811 000 313	811 100 405 811 100 408 811 100 313	85.72
	ESZ-S Panel Mount Alarm continuous/pulsing tone with spades (90 dB)	24 V AC/DC 48 V AC/DC 110/120 V AC 230/240 V AC	809 000 405 809 000 408 809 000 310 809 000 313	809 100 405 809 100 408 809 100 310 809 100 313	108.28
	ESZ-K Panel Mount Alarm continuous/pulsing tone with terminal (90 dB)	24 V AC/DC 48 V AC/DC 110/120 V AC 230/240 V AC	809 010 405 809 010 408 809 010 310 809 010 313	809 110 405 809 110 408 809 110 310 809 110 313	108.28
	BU2 Panel Mount Alarm pulsing tone (90 dB) ①	12 V AC/DC 24 V AC/DC		B100 520 404 B100 520 405	22.56
	BU3 pulsing tone (90 dB) ①	220 V AC		B100 520 313	22.56

BU1 Surface Mount Alarms



	Surface Mount Alarm Electronic Siren pulsing tone (108 dB)	12 V DC 24 V DC		B100 510 004 B100 510 005	43.31
---	--	--------------------	--	------------------------------	-------

① Adjustable sound pressure.