







Mini Horn-Signal Beacons

CE

Type	Description	Specifications	Catalog Number	Price
	Replace ② with lens color		Grey Housing ①	
	<b>KLL</b> Mini Horn Signal Beacon with cone Steady of Flashing (no bulb) ② ③ 92 dB @ VDC 88 dB @ VAC, 50 Hz	24 V DC 24 V AC, 50 Hz 48 V AC, 50 Hz 230 V AC, 50 Hz	<b>710 11① 005</b> <b>710 11① 105</b> <b>710 11① 108</b> <b>710 11① 113</b>	155.88
	<b>KLF</b> Mini Horn Strobe Beacon with cone Xenon tube included ③ 92 dB @ VDC 88 dB @ VAC, 50 Hz	24 V DC 230/240 V AC, 50 Hz	<b>710 12① 005</b> <b>710 12① 113</b>	236.04
	<b>KDL</b> Mini Horn Signal Beacon without cone Steady of Flashing (no bulb) ② ③ 92 dB @ VDC 88 dB @ VAC, 50 Hz	24 V DC 24 V AC, 50 Hz 48 V AC, 50 Hz 230 V AC, 50 Hz	<b>710 01① 005</b> <b>710 01① 105</b> <b>710 01① 108</b> <b>710 01① 113</b>	160.56
	<b>KDF</b> Mini Horn Strobe Beacon without cone Xenon tube included ③ 92 dB @ VDC 88 dB @ VAC, 50 Hz	24 V DC 230/240 V AC, 50 Hz	<b>710 02① 005</b> <b>710 02① 113</b>	238.54

Mini Horns

CE

Type	Description	Specifications	Catalog Number	Price
			Grey Housing	
	<b>KLH</b> Mini Horn with cone continuous tone 92 dB @ VDC 88 dB @ VAC, 50 Hz	12 V DC 24 V DC 110 V DC 220 V DC 24 V AC, 50 Hz 48 V AC, 50 Hz 230 V AC, 50 Hz	<b>710 100 004</b> <b>710 100 005</b> <b>710 100 010</b> <b>710 100 013</b> <b>710 100 105</b> <b>710 100 108</b> <b>710 100 113</b>	82.58
	<b>KDH</b> Mini Horn without cone continuous tone 92 dB @ VDC 88 dB @ VAC, 50 Hz	12 V DC 24 V DC 220 V DC 24 V AC, 50 Hz 48 V AC, 50 Hz 230 V AC, 50 Hz	<b>710 000 004</b> <b>710 000 005</b> <b>710 000 013</b> <b>710 000 105</b> <b>710 000 108</b> <b>710 000 113</b>	75.23

① To complete the catalog no., replace the ① with one of the following numbers for desired lens color:

1 = Amber, 2 = Red, 7 = Yellow.

② Bulb not included. Order separately on page J39.

③ Other voltages and colors available by special order only. Contact factor for more information.

Non-UL Signaling