




Explosion Proof Signaling Horns



Type	Description	Specifications	Catalog Number	Price
	dHH1 Explosion-proof Signal Horn (105 dB) AC	24 V AC, 50 Hz 42 V AC, 50 Hz 48 V AC, 50 Hz 60 V AC, 50 Hz 110 V AC, 50 Hz 230 V AC, 50 Hz 120 V AC, 60 Hz 240 V AC, 60 Hz	300-000-105 300-000-107 300-000-108 300-000-109 300-000-110 300 000 113 300-000-211 300-000-213	2294.53
	dHH2 Explosion-proof Signal Horn (105 dB) DC	12 V DC 24 V DC 48 V DC 60 V DC 110 V DC 220 V DC	300-000-004 300 000 005 300-000-008 300-000-009 300-000-010 300-000-013	2294.53
	dHHR1 Explosion-proof Signal Horn with telephone call relay	230 V AC, 50 Hz	300 100 113	2294.53
	mHPT Explosion-proof Signal Horn (108 dB) Impact resistant Synthetic Temperature range T5 Zones 1, 2	24 V DC 115 V AC 230 V AC	301 100 005 301 100 110 301 100 113	1729.06
	mHTG Explosion-proof Signal Horn (108 dB) Aluminum Temperature range T5 Zone 1, 2 and 21, 22	24 V DC 230 V AC	302 100 005 302 100 113	2148.44

Signal Bells



Type	Description	Specifications	Catalog Number	Price
	dHW1 Explosion-proof Signal Bell (105 dB) AC	24 V AC, 50 Hz 60 V AC, 50 Hz 110 V AC, 50 Hz 230 V AC, 50 Hz 120 V AC, 60 Hz 240 V AC, 60 Hz	320-000-105 320-000-109 320-000-110 320 000 113 320-000-211 320-000-213	2513.67
	dHW1 Explosion-proof Signal Bell (105 dB) DC	12 V DC 24 V DC 48 V DC 60 V DC 110 V DC 220 V DC	320-000-004 320 000 005 320-000-008 320-000-009 320-000-010 320-000-013	2513.67
	dHWR1 Explosion-proof Signal Bell with telephone call relay	230 V AC, 50 Hz	320 100 113	2943.36

Explosion Proof Signaling